
between top and bottom half of tank (sealant run continuous)

. .



MANUFACTURED BY:

Hanover Concrete Corp.
9129 Fenway Drive
Mechanicsville, VA 23111
(804) 648-9259
Loui Heindl, Jr.

TWO-PIECE, ONE-COMPARTMENT SEPTIC TANK
Manufacturer's name, state serial number (if applicable), address (if applicable), and liquid capacity imprinted to the right of the knockout on the outlet end of tank.
LIQUID CAPACITY: 1,028.36 Gallons
LIQUID DEPTH: 48"
FREEBOARD: 12"
LENGTH TO WIDTH RATIO: 2.06 to 1
NUMBER OF INLETS: 3
NUMBER OF OUTLETS: 3
OUTLET MANHOLE: 18" minimum square clearance (with #3 rebar handle) (Weight: 109 lbs.)
INLET MANHOLE: 18" minimum square clearance (with #3 rebar handle) (Weight: 109 lbs.)
INLET TEE OR BAFFLE: TEE: Sanitary tee extending 9" above liquid level and 6" into liquid level (poured monolithic with tank)
OUTLET TEE OR BAFFLE: TEE: Sanitary tee extending 9" above liquid level
and 17" into liquid level (poured monolithic with tank)
BAFFLE OR PARTITION WALL: N/A
CONCRETE: 3000 PSI minimum
REINFORCING: 6"x6"x10/10 wire mesh centered in all walls, ends, baffle
or partition wall, top and bottom
SEALANTS: 1" Butyl Rubber Mastic Sealant in tongue and groove jointline
between top and bottom half of tank (sealant run continuous)

